



CSC880 STAIRCLIMBER



CSC880 StairClimber- Compact Footprint. Maximum Power. Elite Performance.

Built for light commercial use, the CSC880 StairClimber features a heavy-duty steel frame with plastic coverings for added durability. Its seven ABS-lined steps offer reliable grip, each measuring 18"W x 11"D x 7"H (45W x 28D x 18H cm). Engineered for user safety, comfort, and performance, this unit requires a minimum ceiling clearance of 9' (2.7 m) and delivers dependable functionality across various facility types.

Powered by an EMS magnetic control wheel and a chain and Poly-V belt drive system, the CSC880 offers smooth, low-maintenance operation. With 20 levels of magnetic resistance and speeds ranging from 25 to 157 steps per minute, it supports a wide spectrum of training styles—from light cardio to high-intensity intervals. Pre-loaded with programs including fat burn, challenge, and rolling hills, plus three target options, it adapts easily to diverse fitness goals.

A 4.5" LED display with six windows delivers real-time feedback on metrics like METS, watts, vertical distance, steps per minute, and calories burned. Hand pulse sensors, an emergency stop, and intuitive controls add safety and ease of use, while built-in amenities like a cooling fan, accessory rack, and transport wheels enhance convenience.

Fitted with ergonomic, grip-coated steel handrails and powered by a 120V/15A universal AC adapter with a 79" (200 cm) cord, the CSC880 is installation-friendly and versatile. Backed by a 10-year frame warranty, it's a long-term, high-value cardio solution for commercial fitness environments.

CSC880 STAIRCLIMBER

- Durable steel frame with 7 ABS steps
- Large step surface area, 18" L x 11" W x 7" H (45L x 28W x 18H cm)
- 20 levels of resistance with step rate of 25 - 157 steps per minute
- 10 pre-loaded programs
- Contact heart rate grips, resistance controls, and start/stop/pause button on handlebars
- Reading/accessory rack



CSC880 STAIRCLIMBER

EQUIPMENT SPECIFICATIONS

Console	Multi-window white LED display with built in fan, integrated tablet rack, and space for accessories
Programs	Warm up, fat burn, training, rolling hills, challenge, interval, target (3 options), user program
Heart Rate	Hand pulse sensors
Resistance	20 levels
Step Dimensions	18"D x 11"W x 7"H (12" initial step-up height) / 45D x 28W x 18H cm (30 cm initial step-up height)
Power	AC adapter; 120V/15A, 78.7" (200 cm) cord length
Step Rate	25 to 157 steps per minute
Remote Buttons	Resistance up/down, start/stop/pause
Minimum Ceiling	9 ft (2.7 m)
Frame	Commercial-grade steel with plastic shrouds and maintenance access panels
Dimensions	63" L x 31" W x 79" H, 418 lb (159L x 79 W x 200 H cm, 190 kg)
Packaging	57" L x 33" W x 43.9" H, 506 lb (146L x 83W x 111.5H cm, 230 kg)
Max User Weight	330 lb (150 kg)

WARRANTY INFORMATION

Light Commercial (Non-Dues Paying Facility) – Frame: 10 Years, Brake/Parts: 5 Years, Labour: 2 Years, Wear Items: 6 Months